



MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

SECTION I - IDENTIFICATION

PRODUCT NAME : Pro Installer Gun Cleaner
PRODUCT CODE : 4310 Pro installer Gun Cleaner
DESCRIPTION : Polyurethane Foam Gun Cleaner

H.M.I.S RATINGS:

H	F	R	P
1	4	3	G

HAZARDOUS CLASSIFICATION: 2.1
PROPER SHIPPING NAME : Aerosol, Flammable, N.O.S., Butane UN1950
SHIPPING DESCRIPTION : Aerosol, Flammable, N.O.S., Butane UN1950

SECTION II - MANUFACTURER

MANUFACTURER'S NAME : Schnee-Morehead, Inc.
STREET ADDRESS : 111 North Nursery Road, Irving, Texas
INFORMATION PHONE : 972-438-9111 **EMERGENCY PHONE** : 800-424-9300
DATE PREPARED : March 10, 2010 **SUPERSEDES DATE** : March 6, 2007

SECTION III - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER LIMITS	PERCENT (WGT)
Acetone	67-64-1	1000 ppm TWA	500 ppm TWA		>60
Propane	74-98-6	1000 ppm TWA	2500 ppm TWA		10-15
Butane	106-97-8	N.A.	800 ppm TWA		10-15

SECTION IV - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (H₂O=1) : 0.75 **BOILING POINT** : 131°F
NONVOLATILE (% WEIGHT) : N.A. **MELT/FREEZE PT** : N/A
SOLUBILITY IN WATER : Miscible **VAPOR DENSITY** : N/A
EVAPORATION RATE (BuAc=1) : N.A. **VAPOR PRESSURE** : 3.5 bar @ 68°F
VOLATILE ORGANIC CONTENT : N.A.
APPEARANCE/ODOR : Aerosol, transparent color, acetone odor

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : -2.0°F **METHOD USED** : N.A.
FLAMMABLE LIMITS IN AIR BY VOLUME **LOWER** : 2.1% **UPPER** : 13%

EXTINGUISHING MEDIA : Use carbon dioxide or dry chemical. Do not use water.

SPECIAL FIREFIGHTING PROCEDURES : Firefighters should wear a self-contained breathing apparatus and full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARD : Solvent and gas fumes can form explosive mixture in combination with air. fumes are heavier than air and can move along the floor. Use only in well ventilated areas. Do not spray in the direction of a flame or incandescent material. Do not smoke during application. Do not expose to temperatures over 122°F. Danger of bursting exists when containers are heated. Protect against electrostatic charges.

SECTION VI - REACTIVITY DATA

STABILITY : Reaction at high temperature may be violent.

CONDITIONS TO AVOID : Avoid heat and do not expose to temperatures exceeding 122°F. Store in a cool dry location in closed packing at temperatures below 122°F. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurized container: protect from sunlight.

INCOMPATIBILITY (MATERIALS TO AVOID) : Avoid contact with oxidizing agents, bases and acids.



MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

SECTION XI - DISCLAIMER

This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

A MSDS such as this cannot be expected to cover all possible individual situations. The end user of this product has the responsibility to provide a safe workplace. All aspects of an individual operation should be examined to determine if, or where, precautions – in addition to those described herein – are required. Any health and safety information contained herein should be passed on to your customers and/or employees.

The opinions expressed herein are those of qualified experts within Schnee-Morehead®, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the use of this product are not within the control of Schnee-Morehead®, Inc., final determination of suitability of this product is the sole responsibility of the user. It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.

=====
N/A = Not Applicable, N.A. = Not Available, N.D. = Not Determined, N/E = Not established, UNK = Unknown