



# Tacky Tape<sup>®</sup>

## SM5228

### Industrial Butyl Tape

## TECHNICAL DATA

### PRODUCT DESCRIPTION:

**SM5228 TACKY TAPE<sup>®</sup>** is a 100% solids, non-hardening, crosslinked butyl base tape sealant. SM5228 has been specifically designed with aggressive tack and high internal tensile strength. This tape gives an immediate and permanent bond without the need of a primer, to a wide range of substrates. The substrates include, but are not limited to ABS, fiberglass, aluminum, glass, steel and wood. The material is black in color and extruded on a removable release liner to conform to specified dimensional tolerances.

### TYPICAL USES:

- Temporarily holds fixtures and wall panel systems and structures in bathrooms and kitchens
- Bonds acrylic bath tub and wall liners, shower bases, doors and walls
- Temporarily bonds road reflectors to pavement
- Permanently seals and protects low voltage tap, feeder and splice connections both above and below ground level.

### ADVANTAGES:

- Easy to apply by hand (User friendly)
- Permanently flexible, non-shrinking and non-corrosive
- No primer is required
- Resists fungal attack and will not support mildew growth
- Wide application temperature
- Aggressive tack to a wide range of substrates
- Supplied as preformed tape in roll form

### SPECIFICATION COMPLIANCE:

AAMA 807.3-92 (reference standard AAMA 800-92)

### TYPICAL PROPERTIES:

|                               |   |                    |
|-------------------------------|---|--------------------|
| BASE POLYMER:                 | Crosslinked Butyl   | Determined by FTIR |
| PERCENT SOLID:                | 100%  |                    |
| COLOR:                        | Black   |                    |
| WEIGHT/GALLON:                | 11.23 LBS/GALLON (1.35 Kg/L)  | ASTM D792          |
| SAG RESISTANCE                | None  | AAMA 800-92        |
| VEHICLE MIGRATION             | None  | AAMA 800-92        |
| WATER RESISTANCE              | Excellent   | AAMA 800-92        |
| HARDNESS (Shore OO)           | 60-80   | AAMA 800-92        |
| ELONGATION                    | 300% Minimum  | ASTM C908          |
| LOW TEMPERATURE FLEXABILITY   | Pass @ 0°F (-18°C)  | ASTM C765          |
| YEILD STRENGTH                | 10-18 PSI   | AAMA 800-92        |
| LAP SHEAR STRENGTH            | 6 PLI Minimum   | ASTM C961          |
| APPLICATION TEMPERATURE RANGE | 0°F (-18°C) to 120°F (49°C)   |                    |
| SERVICE TEMPERATURE RANGE     | -25°F (-32°C) to 180°F (82°C)   |                    |
| FREIGHT CLASSIFICATION:       | Caulking Compound, NOIBN (NO LABEL REQUIRED)  |                    |
| STORAGE:                      | Keep in cool dry place. SM5228 Tacky Tape <sup>®</sup> has a one year shelf life from date of manufacture when stored at or below 80°F (27°C) |                    |

**PACKAGING:**

SM5228 Tacky Tape® sealant is supplied in roll form with a special release paper. This product is available through Schnee-Morehead® Customer service department at 1-800-Trust SM (878-7876).

**EXCLUSION OF WARRANTIES:**

AS TO THE HEREIN DESCRIBED MATERIALS, SCHNEE-MOREHEAD®, INC. MAKES NO WARRANTIES WHETHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SINCE THE USE OF THE HEREIN DESCRIBED MATERIALS INVOLVES MANY VARIABLES IN METHODS OF APPLICATION, HANDLING AND/OR USE, THE USER IN ACCEPTING AND USING THESE MATERIALS ASSUMES ALL RESPONSIBILITY FOR THE END RESULT. THE PURCHASE OF THIS SCHNEE-MOREHEAD®, INC. PRODUCT IS SUBJECT TO THE TERMS AND CONDITIONS OF AN "AS IS" SALE, AND IF THE PRODUCT IS PROVED TO BE DEFECTIVE, THE EXCLUSIVE REMEDY, AT SCHNEE-MOREHEAD®, INC.'S OPTION, SHALL BE TO REPLACE THE DEFECTIVE SCHNEE-MOREHEAD®, INC. PRODUCT. SCHNEE-MOREHEAD®, INC. SHALL NOT OTHERWISE BE LIABLE FOR LOSS OF DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL, REGARDLESS OF THE LEGAL THEORY ASSERTED, INCLUDING NEGLIGENCE, WARRANTY OR STRICT LIABILITY.

Complete technical information is available from Schnee-Morehead®, Inc. For technical assistance, customer service and general information call:

**1-800-TRUSTSM**  
**1-800-878-7876**

**SCHNEE-MOREHEAD®, INC.**  
111 N. Nursery Road  
Irving, TX 75060  
972-438-9111 Fax: 972-554-3939  
[www.trustsm.com](http://www.trustsm.com)