



**Tacky Tape<sup>®</sup>**  
**SM5229**  
**Room Temperature**  
**Debulking Tape Sealant**

**PRODUCT DESCRIPTION:**

SM5229 Tacky Tape<sup>®</sup> has been used in the aerospace industry and composite manufacturing as a debulking tape in vacuum bag applications that require no heating or curing. The tape is formulated to seal most films to tools while positive vacuum is held for room temperature applications.

**ADVANTAGES:**

- Easy to apply by hand (User friendly)
- Tenacious adhesion to most films and tool surfaces
- Room temperature applications
- Strips clean from tool surfaces at room temperature
- Non-hazardous
- Use for multiple debulking cycles without reapplication

**TYPICAL PROPERTIES:**

COLOR:	Grey
PERCENT SOLID:	100%
CONSISTENCY: Cone Penetration	85-105 300 GRAM LOAD ASTM D-217
WEIGHT/GALLON:	12.3 LBS/GAL (1.47Kg/L)
FREIGHT CLASSIFICATION:	Caulking Compound, NOIBN (NO LABEL REQUIRED)
STORAGE:	Keep in a cool dry place. SM5229 Tacky Tape <sup>®</sup> has an 18 month shelf life from date of manufacturer when stored at or below 80°F (27°C). Do not store cartons on end, keep flat.

**PERFORMACE TEMPERATURE RANGE:**

Application Temperature Range: 45°F (7°C) to 120°F (49°C)  
 Service Temperature Range: 45°F (7°C) to 120°F (49°C)

**APPLICATION:**

Apply by hand to a clean dry tool or platen with release paper on top. When the sealant is in position remove the release paper and lay the film on top. Apply pressure by hand or roller on the sealant to obtain maximum adhesion to ensure positive vacuum. SM5229 can be stripped without leaving residue on metal tool surfaces that have been cooled to room temperature (77°F).

**PACKAGING:**

SM5229 Tacky Tape® sealant is supplied in roll form with a special release paper. The tape is available in a variety of sizes. This product is available through Schnee-Morehead's Customer Service Department at 1-800-Trust-SM, (1-800-878-7876).

**EXCLUSION OF WARRANTIES:**

AS TO THE HEREIN DESCRIBED MATERIALS, SCHNEE-MOREHEAD®, INC. MAKES NO WARRANTIES WHETHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SINCE THE USE OF THE HEREIN DESCRIBED MATERIALS INVOLVES MANY VARIABLES IN METHODS OF APPLICATION, HANDLING AND/OR USE, THE USER IN ACCEPTING AND USING THESE MATERIALS ASSUMES ALL RESPONSIBILITY FOR THE END RESULT. THE PURCHASE OF THIS SCHNEE-MOREHEAD®, INC. PRODUCT IS SUBJECT TO THE TERMS AND CONDITIONS OF AN "AS IS" SALE, AND IF THE PRODUCT IS PROVED TO BE DEFECTIVE, THE EXCLUSIVE REMEDY, AT SCHNEE-MOREHEAD®, INC.'S OPTION, SHALL BE TO REPLACE THE DEFECTIVE SCHNEE-MOREHEAD®, INC. PRODUCT. SCHNEE-MOREHEAD®, INC. SHALL NOT OTHERWISE BE LIABLE FOR LOSS OF DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL, REGARDLESS OF THE LEGAL THEORY ASSERTED, INCLUDING NEGLIGENCE, WARRANTY OR STRICT LIABILITY.

Complete technical information is available from Schnee-Morehead®, Inc. For technical assistance, customer service and general information call:

**1-800-TRUSTSM**  
**1-800-878-7876**

**SCHNEE-MOREHEAD®, INC.**

111 N. Nursery Road  
Irving, TX 75060  
972-438-9111 Fax: 972-554-3939

[www.trustsm.com](http://www.trustsm.com)